AGF0062

High-end gelato holding freezer
Armadio frigorifero per gelato

-30°



GENERAL FEATURES
- Stainless steel framework construction·, monocoque structure
- Scotch brite external finish
- 75 mm insulation (high density 40 Kg/mc, CFC and HCFC free)
- Door frame with replaceable electric resistance
- Magnetic gaskets replaceable without tools
- Automatic self-closing REVERSIBLE door
- Compensation valve to ease door openings
- Front hinges for installation on concrete plinths
- Adjustable stainless steel feet
- Rounded corners for better cleaning
- Stainless steel tray supports with pierced diamond pattern to adjust trays' height every 3,5 or 5 cm (standings nr. 36 - 25)

REFRIGERANT UNIT
- Indirect ventilated air circulation system (on sides) with flow conveyor to ensure temperature uniformity and perfect product preservation
- Autom ventilation stop when opening doors, controlled by micro-switch
- Intelligent defrosting: only when needed, electric
- MONOBLOCK cooling system: all in one block above the cabinet
- Quick temperature recovery (to compensate with frequent door openings)
- Evaporator with anticorrosion cataphoresis treatment, with capillar
- Control board with "LAB" function (continuous freezing)

OPTIONS / ACCESSORIES
- Castors available on request - additional guides and shelves
- Available also with water cooled unit

CAPACITY tubs 360x165x120	48	TEMPERATURE RANGE	-30/-12°C	Internal light Door lock	Standard Standard
CAPACITY tubs 360x250x120	32	Internal fittings shelves (included)	5 x (500x700) + 5 coppie guida a "C" + 5 pair of "C" guides	OPTIONS castors cod. BN219901 "C" shape guides cod. FPCG57I Shelves cod. RFI57P	

Caratteristiche - Features

Capacità L. Capacity L.	590	Capacità refrigerazione W Refrigeration capacity W	572* 848**
Dimensioni LxPxH Dimensions WxDxH	700x870x2080	Alimentazione elettrica V/~/Hz Electric power supply V/~/Hz	230/1/50
Luce porta LxH Light door WxH	550x1480	Potenza max W Max. power W	820
Profondità interna mm Inner depth mm	725	Corrente max assorbita A Max. absorbed current A	4,4
Profondità con porta 90° mm Depth with 90° door	1490	Sistema di refrigerazione Refrigeration system	VENTILATED AIR FORCED
Classe climatica Climatic class	T	Dimensione imballo LxPxH Packing dimensions WxDxH	740x890x2200
Temperatura di esercizio °C Operating temperature °C	-30/-12	Volume imballo m3 Packing volume m3	1,45
Refrigerante Refrigerant	R404	Peso netto (net weight) kg Peso lordo (gross weight) kg	135 150

(*) Temp.evap. -10°C, Temp. cond. +45°C - (**) Temp.evap. +7,2°C, Temp.cond. +54.4°C

HIBER—ALI S.p.A.
Via Cal Larga, 8—z.i. San Giacomo di Veglia
31029 Vittorio Veneto (TV) - Italy

Tel. +39 0438 911940
Fax +39 0438 911997

www.hiber.it
info@hiber.it