

AGF0072

High-end gelato holding freezer
Armadio frigorifero per gelato

 -30°



GENERAL FEATURES

- Stainless steel aisi304 framework construction, monocoque structure
- Scotch brite external finish
- 60 mm insulation (high density 40 Kg/mc, CFC and HCFC free)
- Door frame with replaceable electric resistance
- Magnetic gaskets replaceable without tools
- Automatic self-closing REVERSIBLE door
- Compensation valve to ease door openings
- Front hinges for installation on concrete plinths
- Adjustable stainless steel feet
- Rounded corners for better cleaning
- Stainless steel tray supports with pierced diamond pattern to adjust trays' height every 3,5 or 5 cm (standings nr. 38-26)

REFRIGERANT UNIT

- Indirect ventilated air circulation system (frontal) with flow conveyor to ensure temperature uniformity and perfect product preservation
- Autom ventilation stop when opening doors, controlled by micro-switch
- Intelligent defrosting: only when needed, with hot gas
- MONOBLOCK cooling system: all in one block above the cabinet
- Quick temperature recovery (to compensate with frequent door openings)
- Evaporator with anticorrosion cataphoresis treatment, with capillar
- HACCP Control board with "LAB" function (continuous freezing)

OPTIONS / ACCESSORIES

- Castors available on request - extra guides and shelves
- Available also with water cooled unit

CAPACITY
tubs
360x165x120

60

TEMPERATURE RANGE **-30/-12°C**

Internal light
Door lock

Standard
Standard

CAPACITY
tubs
360x250x120

40

Internal fittings shelves
(included) **5 x (600X660)**
+ 5 pair of "C" guides

OPTIONS

Castors cod. BN219901
"C" shape guides cod. FPCG67I
Shelves cod. RLI67G

Caratteristiche - Features

Capacità L. Capacity L.	740	Capacità refrigerazione W Refrigeration capacity W	572* 848**
Dimensioni LxPxH Dimensions WxDxH	740x910x2070	Alimentazione elettrica V/~/Hz Electric power supply V/~/Hz	230/1/50
Luce porta LxH Light door WxH	620x1474	Potenza max W Max. power W	955
Profondità interna mm Inner depth mm	730	Corrente max assorbita A Max. absorbed current A	4,5
Profondità con porta 90° mm Depth with 90° door mm	1600	Sistema di refrigerazione Refrigeration system	VENTILATED AIR FORCED
Classe climatica Climatic class	T	Dimensione imballo LxPxH Packing dimensions WxDxH	780x940x2200
Temperatura di esercizio °C Operating temperature °C	-30/-12	Volume imballo m3 Packing volume m3	1,57
Refrigerante Refrigerant	R404	Peso netto (net weight) kg Peso lordo (gross weight) kg	180 210

(*) Temp.evap. -10°C, Temp. cond. +45°C - (**) Temp.evap. +7,2°C, Temp.cond. +54.4°C

HIBER—ALI S.p.A.
Via Cal Larga, 8—z.i. San Giacomo di Veglia
31029 Vittorio Veneto (TV) - Italy

Tel. +39 0438 911940
Fax +39 0438 911997

www.hiber.it
info@hiber.it

