



HOBART GMBH
PRODUCT OVERVIEW

FOOD PREPARATION



POTATO AND VEGETABLE PEELER



6115

6430

BEST RESULTS

The HOBART peelers are able to peel a full load of potatoes, carrots or other root vegetables in 3 minutes or less. The peeling element is a lightweight fiberglass reinforced plastic disc with silicon-carbide abrasive permanently bonded to the disc that gives you controlled peeling at its finest. The peelers include an electrical motor and a synchronous timer that is adjustable for any increments from 30 seconds to up to 5 minutes.

EASY HANDLING – HYGIENIC

A one-piece, easily removable, positive locking hopper cover is provided for easy cleaning. The water inlet is an air-gap type at a sufficient height to meet plumbing codes. Incoming water strikes the curved surface of the hopper cover, promoting interior self-cleaning and preventing undesirable splash. The peeling element can easily and quickly be removed for cleaning. Each unit is easy to use with simple switches.

DESIGN – QUALITY

The peeler unit is a cylindrical construction of heliarc-welded stainless steel with removable Lexan liner. Durable, reliable motors guarantee a long life time. Speed reduction between motor and peeling disc is obtained directly through a dual V-belt. The housing as well as the drive shaft are made of stainless steel.

SAFETY

An advanced designed triple protection sealing prevents entrance of water into the shaft bearings. The motor features a manual reset thermal overload protection. An interlock prevents the machine from being turned on unless the bowl cover is down and locked in place.

TECHNICAL DATA

MODEL	6115	6430
CAPACITY in kg	6.8	13.6
POWER SUPPLY	230 / 50 / 1	230 / 50 / 1 400 / 50 / 3
TOTAL LOADING in kW	0.25	0.56
SPEED in rpm	1,425	1,425
DIMENSIONS H x W x D in mm	690 x 480 x 590	810 x 620 x 730
NET WEIGHT in kg	26	67



HOBART GMBH

Robert-Bosch-Straße 17 | 77656 Offenburg | Germany

Phone: +49(0)781.600-28 20 | Fax: +49(0)781.600-28 19

E-Mail: info-export@hobart.de | Internet: www.hobart-export.com

Member of the ITW Food Equipment Group Europe

